

*“Where your transactions
meet our technology.”*

CashNCoin CM-1000 SERIES

The new coin deposit module
attachment for the TRT-2000 ATM



TRANTECH
ATM

CM-1000 Features

Compact & efficient design

- Cost efficient coin counting solution
- Low cost by working as a sidecar for TRT-2000 ATM
- Space saving design
- Maintenance friendly design (top & front doors)

Convenient & Safe

- Counting speed up to 600 coins/min
- Automatic Open/Close shutter to prevent access to feeding belt
- Optical sensor to prevent an over-flow feeding
- Bar code printed on a receipt
- Your own surcharge rate
- Automatic locking system when the deposit box is removed
- Graphic prompts for errors on TRT-2000's 10.4 inch TFT LCD
- User friendly interface

Precise counting

- Retract function for a cancelled transaction
- Fabricated coin detection
- Defective coin detection
- Detection of all metal objects
- Detection range: Diameter 18-26.5 mm, Thickness 1.2-1.9 mm
- Electro-magnetic sorting mechanism
- Belt carriage system



Coin Module Specifications

Denomination	1 / 5 / 10 / 25 / 50 cent, & \$1.00 coins
Coin carriage	Belt
Processing capacity	10 coin / Sec (600 coin / Min)
Transaction capacity	500 / transaction (based on 25 cent)
Deposit container	Capacity: 4,000~6,000 (based on 25 cent) Security: Container auto-closed when removed
Retract bin capacity	500 coin (based on 25 cent)
Over-flow sensor	Over-flow detection by Optical sensor
Temporary stacker	Retract to the reject bin by bulk when transaction cancelled or error occurred (Capacity 350 coin, based on 25 cent)
Service type	Front Service (Rear Service : PSU & Control B/D)
Size (in)	13"(W) x 41.75"(H) x 24"(D)
Weight (lbs)	About 220 lbs
Power (v)	110vac or 220vac
Power Consumption	AC 220v 60w
Communication Cable	RS232 Serial
Environment	On operation : Temperature 50°F ~ 95°F Relative Humidity 40 ~ 60% In Stock : Temperature 32°F ~ 104°F Relative Humidity 30 ~ 80%

